

Printing date 17.07.2014 Version number 10 Revision: 30.06.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

- · Trade name: Dinitrol Penetrant LT Spray
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Anticorrosion additive
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

DINOL GmbH Pyrmonter Str. 76 D-32676 Lügde Tel: +49 5281 9829 80

Tel: +49 5281 9829 80 Fax: +49 5281 9829 860 E-mail: msds@dinol.com

- · Further information obtainable from: Research & Development
- · 1.4 Emergency telephone number:

Giftnotruf Berlin +49(0)30 30686 790 Beratung in Deutsch und Englisch.

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xi; Sensitising

R43: May cause sensitisation by skin contact.



F+; Extremely flammable

R12: Extremely flammable.

R66-67: Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent. Warning! Pressurized container.

Has a narcotizing effect.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data

· 2.2 Label elements

· Labelling according to EU guidelines:

The product has been marked in accordance with EU Directives / respective national laws.

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

The R and S phrases may be omitted if packaging contains no more than 0.125 litre.

· Code letter and hazard designation of product:

Xi Irritant

F+ Extremely flammable

· Hazard-determining components of labelling:

Calcium Sulfonate

· Risk phrases:

12 Extremely flammable.

43 May cause sensitisation by skin contact.

66 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 2)



Printing date 17.07.2014 Version number 10 Revision: 30.06.2014

Trade name: Dinitrol Penetrant LT Spray

(Contd. of page 1)

67 Vapours may cause drowsiness and dizziness.

· Safety phrases:

- 2 Keep out of the reach of children.
- 16 Keep away from sources of ignition No smoking.
- 23 Do not breathe vapour/spray.
- 24 Avoid contact with skin.
- 37 Wear suitable gloves.
- 51 Use only in well-ventilated areas.
- 60 This material and its container must be disposed of as hazardous waste.

· Special labelling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Buildup of explosive mixtures possible without sufficient ventilation.

- · Classification in accordance with Directive 75/324/EEC: Extremely flammable
- · 2.3 Other hazards

The petroleum naphtha / petroleum distillate / lubricating oil meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with additions.

| Dangerous components: | | |
|--|---|---------|
| CAS: 64742-48-9 EC number: 919-857-5 Reg.nr.: 01-2119463258-33 | Naphtha (petroleum), hydrotreated heavy Xn R65 R10-66-67 ♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336 | 25-<50% |
| CAS: 74-98-6 EINECS: 200-827-9 | Propane liquefied F+ R12 Flam. Gas 1, H220; Press. Gas, H280 | 10-<25% |
| CAS: 106-97-8 EINECS: 203-448-7 | Butane, pure ★ F+ R12 ♦ Flam. Gas 1, H220; ♦ Press. Gas, H280 | 10-<25% |
| CAS: 64742-48-9 EINECS: 265-150-3 | Naphtha (petroleum), hydrotreated heavy Xn R65 R10-66-67 ♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336 | 1-<5% |
| CAS: 61789-86-4 | Calcium Sulfonate | 1-<5% |

[·] Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)



Printing date 17.07.2014 Version number 10 Revision: 30.06.2014

Trade name: Dinitrol Penetrant LT Spray

(Contd. of page 2)

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents:

Water

Water with full jet

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.
- · Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Absorb liquid components with liquid-binding material.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Use only in well ventilated areas.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Do not seal receptacle gas tight.

(Contd. on page 4)



Printing date 17.07.2014 Version number 10 Revision: 30.06.2014

Trade name: Dinitrol Penetrant LT Spray

(Contd. of page 3)

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

| · Ingredients with limit values that require monitoring at the workplace: | | | |
|---|---|--|--|
| 106-9 | 106-97-8 Butane, pure | | |
| WEL | Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm | | |
| | Long-term value: 1450 mg/m³, 600 ppm | | |
| | Carc (if more than 0.1% of buta-1.3-diene) | | |

· DNELs

64742-48-9 Naphtha (petroleum), hydrotreated heavy

| UT/ T2-TU- | 04742-40-> Ivapuna (penoteum), nyaroneateu neuvy | | |
|------------|--|---------------------------------------|--|
| Oral | Acute - systemic effects, general population | 125 mg/kg bw/day (General Population) | |
| Dermal | Acute - systemic effects, general population | 125 mg/kg (General population) | |
| | Long-term - systemic effects, worker | 208 mg/kg bw/day (Worker) | |
| Inhalative | Acute - systemic effects, general population | 900 mg/m3 (General Population) | |
| | Long-term - systemic effects, worker | 871 mg/m3 (Worker) | |

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use suitable respiratory protective device in case of insufficient ventilation.

· Protection of hands:



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber

Recommended thickness of the material: ≥ 0.12 mm

· Penetration time of glove material

> 480 min.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

(Contd. of page 4)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.07.2014 Version number 10 Revision: 30.06.2014

Trade name: Dinitrol Penetrant LT Spray

· Eye protection:



Tightly sealed goggles

| SECTION 9: P | hysical | and cl | hemical | pro | perties |
|--------------|---------|--------|---------|-----|---------|
|--------------|---------|--------|---------|-----|---------|

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Aerosol
Colour: Light beige
Odour: Characteristic
Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: -44 °C

Flash point: < -20 °C (DIN 53213)

· Flammability (solid, gaseous): Not applicable.

• Ignition temperature: $> 200 \, ^{\circ}C$

· Decomposition temperature: Not determined.

· Self-igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapour

mixtures are possible.

· Explosion limits:

 Lower:
 0.6 Vol %

 Upper:
 10.9 Vol %

· Vapour pressure At 20 °C: 4500 hPa

Density At 20 °C:

0.818 g/cm³ (DIN 51757)

Relative density
 Vapour density
 Evaporation rate
 Not determined.
 Not applicable.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined.

Kinematic: Not determined.

· Solvent content:

Organic solvents: 72.8 %

Solids content: 27.2 % (DIN 53216)

• 9.2 Other information No further relevant information available.

· VOC (EU): 72.83 % · VOC (EU): 595.7 g/l

(Contd. on page 6)



Printing date 17.07.2014 Version number 10 Revision: 30.06.2014

Trade name: Dinitrol Penetrant LT Spray

(Contd. of page 5)

· **VOCV:** 72.83 %

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:

| | · Acute toxicity: | | | |
|---|--|--|----------------------|--|
| | · LD/LC50 values relevant for classification: | | | |
| Ī | 64742-48- | 64742-48-9 Naphtha (petroleum), hydrotreated heavy | | |
| İ | Oral | LD50 | >5000 mg/kg (RAT) | |
| | Dermal | LD50 | >5000 mg/kg (RABBIT) | |
| | Inhalative | LC50/4 h | > 4951 mg/l (RAT) | |
| Ī | 106-97-8 I | 106-97-8 Butane, pure | | |
| Ī | Inhalative | LC50/4 h | 658 mg/l (rat) | |
| Ī | 64742-48-9 Naphtha (petroleum), hydrotreated heavy | | | |
| Ī | Oral | LD50 | >5000 mg/kg (RAT) | |
| | Dermal | LD50 | >3000 mg/kg (RAT) | |
| | | | | |

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 7)



Printing date 17.07.2014 Version number 10 Revision: 30.06.2014

Trade name: Dinitrol Penetrant LT Spray

(Contd. of page 6)

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- European waste catalogue
 16 00 00 WASTES NOT OTHERWISE SPECIFIED IN THE LIST
 16 05 00 gases in pressure containers and discarded chemicals
 16 05 04* gases in pressure containers (including halons) containing dangerous substances
 - · Uncleaned packaging:
 - · Recommendation: Disposal must be made according to official regulations.

| 14.1 UN-Number | UNIOSO | |
|-----------------------------------|---------------------|--|
| ADR, IMDG, IATA | UN1950 | |
| 14.2 UN proper shipping name | | |
| ADR | 1950 AEROSOLS | |
| IMDG | AEROSOLS | |
| IATA | AEROSOLS, flammable | |
| 14.3 Transport hazard class(es) | | |
| ADR | | |
| | | |
| 2 | | |
| Class | 2 5F Gases. | |
| - Label | 2.1 | |
| · IMDG, IATA | | |
| | | |
| | | |
| 2 | | |
| Class | 2.1 | |
| Label | 2.1 | |
| 14.4 Packing group | | |
| ADR, IMDG, IATA | Void | |
| 14.5 Environmental hazards: | | |
| Marine pollutant: | No | |
| 14.6 Special precautions for user | Warning: Gases. | |
| Danger code (Kemler): | - | |
| EMS Number: | F- D , S - U | |

(Contd. on page 8)



Printing date 17.07.2014 Version number 10 Revision: 30.06.2014

Trade name: Dinitrol Penetrant LT Spray

| | (Contd. of page 7 |
|--|--|
| Transport/Additional information: | For ADR and IMDG: Transport and packing are in accordance with the regulation for limited quantities. These products are therefore classified as no dangerous goods. |
| ADR | |
| Limited quantities (LQ) | 1L |
| Excepted quantities (EQ) | Code: E0 |
| | Not permitted as Excepted Quantity |
| Transport category | 2 |
| Tunnel restriction code | D |
| IMDG | |
| Limited quantities (LQ) | 1L |
| Excepted quantities (\widetilde{EQ}) | Code: E0 |
| · · · · · | Not permitted as Excepted Quantity |

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Labelling according to EU guidelines:

The product has been marked in accordance with EU Directives / respective national laws.

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

The R and S phrases may be omitted if packaging contains no more than 0.125 litre.

· Code letter and hazard designation of product:

Xi Irritant

F+ Extremely flammable

· Hazard-determining components of labelling:

Calcium Sulfonate

· Risk phrases:

- 12 Extremely flammable.
- 43 May cause sensitisation by skin contact.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

· Safety phrases:

- 2 Keep out of the reach of children.
- 16 Keep away from sources of ignition No smoking.
- 23 Do not breathe vapour/spray.
- 24 Avoid contact with skin.
- 37 Wear suitable gloves.
- 51 Use only in well-ventilated areas.
- 60 This material and its container must be disposed of as hazardous waste.

· Special labelling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Buildup of explosive mixtures possible without sufficient ventilation.

· Classification in accordance with Directive 75/324/EEC: Extremely flammable

(Contd. on page 9)



Printing date 17.07.2014 Version number 10 Revision: 30.06.2014

Trade name: Dinitrol Penetrant LT Spray

(Contd. of page 8)

- · National regulations:
- · Technical instructions (air):

| Class | Share in % |
|-------|------------|
| NK | 72.8 |

- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

R10 Flammable.

R12 Extremely flammable.

R43 May cause sensitisation by skin contact.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

- · Department issuing MSDS: Research & Development
- · Contact: Kontakt: msds@dinol.com oder Tel.: 0049 (0)5281 982 980
- * Data compared to the previous version altered.

GB